



## CAT 305E2 Excavator

Available for  
hire.

Short or Long  
term use.

Mine Site or  
Civil Project.

Contact Jemrok  
today.



# CAT 305E2 Capabilities

## Engine

Engine Model*	Cat C2.4	
Rated Net Power @ 2,200 rpm ISO 9249/IEC 601269	30 kW	40.2 hp
Gross Power ISO 14396	31.2 kW	41.8 hp
Bore	87 mm	3.4 in
Stroke	102.4 mm	4 in
Displacement	2.4 L	146 in <sup>3</sup>

\*Meets U.S. EPA Tier 4 Final/EU Stage IIIA emission standards.

## Weights\*

Weight – Canopy, Standard Stick	4975 kg	10,970 lb
Weight – Canopy, Long Stick	5020 kg	11,069 lb
Weight – Cab, Standard Stick	5140 kg	11,334 lb
Weight – Cab, Long Stick	5185 kg	11,443 lb

\*Weight includes counterweight, rubber tracks, bucket, operator, full fuel and auxiliary lines.

# Contact Us

David Cooper

Engineering Manager

ph: 03 6442 2699

m: 0437 100 299

e: [david.cooper@jemrok.com.au](mailto:david.cooper@jemrok.com.au)

Scott St Clair

Operations Manager

ph: 03 6442 2699

m: 0439 321 738

e: [scott@jemrok.com.au](mailto:scott@jemrok.com.au)

# 305E2 dimensions

## Dimensions

	Standard Stick		Long Stick	
	mm	in	mm	in
1 Dig Depth	3280	129	3670	144
2 Vertical Wall	2320	91	2630	104
3 Maximum Reach at Ground Level	5330	210	5810	229
4 Maximum Reach	5600	220	5960	235
5 Maximum Dig Height	5250	207	5440	214
6 Maximum Dump Clearance	3720	129	3920	154
7 Boom In Reach	2350	93	2530	100
8 Tail Swing	1100	43	1100	43
9 Maximum Blade Height	405	16	405	16
10 Maximum Blade Depth	555	22	555	22
11 Boom Height in Shipping Position	1750	69	2150	85
12 O/A Shipping Height	2550	100	2550	100
13 Swing Bearing Height	615	24	615	24
14 O/A Undercarriage Length	2580	102	2580	102
15 O/A Shipping Length	5180	204	5290	208
16 Boom Swing Right	785	31	785	31
17 Boom Swing Left	695	27	695	27
18 Track Belt/Shoe Width	400	16	400	16
19 O/A Track Width	1980	78	1980	78

